



## BioWood® Garage Doors

**If you're ready to draw the line at average and reach for better call us today.**

To locate Steel-Line branches across Australia call: **1300 427 243** or visit [steel-line.com.au](http://steel-line.com.au)

Steel-Line's BioWood® garage door retains the natural timber look and feel, is low maintenance and meets the standard for fire safety under BAL-29 conditions.

There are several good reasons to choose a BioWood® garage door for your home. The BioWood® wood composite products are created using 0.85 density natural cellulose fibre from plantation harvested timber combined with a specially formulated resin. It retains the aesthetic natural look and feel of wood, is lightweight, provides a high degree of water resistance, does not bleach, split, crack, and is suitable for both bushfire regions up to BAL-29 rating and marine applications. The product is termite resistant, low maintenance and is green certified by Global Green Tag. It is the perfect durable product for all building applications.

With the BioWood® sanded finish and unique coating process, these doors are not only beautiful to look at, but are also robust, versatile and designed to withstand the harsh Australian climate.








## Why you should choose a Biowood® garage door

- Biowood® cladding meets the requirement for bush fire resisting timber and is deemed to be acceptable to withstand exposure up to BAL-29 conditions, as specified in AS3959-2018 Construction of Buildings in bushfire prone areas Appendix F
- Retains the natural aesthetic timber look and feel
- Light weight
- Designed to withstand the harsh Australian climate - no splinters, cracks, warping, cupping or rot
- Durable – water, mould, mildew, and termite resistant
- Time tested suitability for marine, intertidal and salt spray environment
- UV stable under normal environmental conditions, even in full sun, when coated with Biowood® water based coating
- Easy and concealed installation
- Virtually maintenance free – depending on north orientation, coating will last for 3 times longer than normal UV coating
- Environmentally friendly – sustainable timber alternative, fully recyclable
- Can be re-sanded & re-sealed
- Option to stain in variety of colours
- Trusted brand by Global Green Tag

## Profile and Colour Options

Providing Australian homeowners with both durability and style, the Biowood® garage doors come in two attractive colours: Spotted Gum and Weatherwood.

These garage doors are constructed using Biowood® architectural profiles and are available in 150mmx18mm Shiplap and 88mmx12mm Tongue & Groove profiles.

Profiles	Colours	
	Spotted Gum	Weatherwood
<p>150mmx18mm Shiplap</p> 		
<p>88mmx12mm Tongue &amp; Groove</p> 		N/A

**NOTE** The colours shown are a guide only. The limitations of printing processes make extremely accurate matches impossible. We strongly recommend comparing your choice with actual samples. As Biowood® is a predominately natural product, variations in colour and finish may be evident. Additionally, Steel-Line reserves the right to vary or delete colours without notice.

Proudly distributed by:

